

RFND



HEAVY DUTY AIRLESS SPRAY PAINTING EQUIPMENT

The range is designed for tough working conditions and suitable for high viscosity, solventless, low solvent coating, semisolid coating, marine coating, and all types of sprayable pumps.

FEATURES

- Pneumatically sensed stall free high performance Air Motor
- High Flow Rate
- Stainless Steel rust proof Hydraulic Body
- Easy Maintenance
- Ice free Air Motors
- Light and Easy to handle
- Compliance to EC Norms



h II B T4 Gb

ACCESSORIES



TECHNICAL SPECIFICATIONS

Type	35.275	50.210	55.275	60.180	70.150	75.210	75.275
Ratio*	35:1	50:1	55:1	60:1	70:1	75:1	75:1
Output per Cycle	275 cc	210 cc	275 cc	180 cc	150 cc	210 cc	275 cc
Air Motor Piston Ø	250 mm	250 mm	300 mm	250 mm	250 mm	300 mm	350 mm
Stroke Length	120 mm	120 mm	120 mm	120 mm	120 mm	120 mm	120 mm
Recommended Spray Volume@ 25 cycles per min	6.8 ltr.	5.25 ltr.	6.8 ltr.	4.5 ltr.	3.75 ltr.	5.25 ltr.	6.87 ltr.
Air Inlet Pressure Max.	7 bar	7 bar	7 bar	7 bar	6 bar	6 bar	6 bar
Output Pressure Max.	245 bar	350 bar	385 bar	420 bar	420 bar	450 bar	450 bar
Air Consumption N ltr / min at 25 cycles/min	2400	2400	3400	2400	2100	3000	4100

*Other ratios and flow on request

Authorized Distributor

CLEAN BLAST

CLEAN BLAST INTERNATIONAL (L.L.C)

P.O.Box: 93716, Dubai Investment Park 2
 Dubai-United Arab Emirates
 +971 4 884 7344
 sales@cleanblast.com
 www.cleanblast.com

Abu-Dhabi-U.A.E	Tel: +971 2551 3815
Doha-Qatar	Tel: +974 4469 7562
Kuwait	Tel: +965 9954 3676
Dammam-Saudi Arabia	Tel: +971 4884 7344
India-Cochin	Tel: +91 48423 56660
India-Bangalore	Tel: +91 95447 28000
Malaysia- Kuala Lumpur	Tel: +603 8957 7553